







Delta BreezGreenBuilder



Delta BreezGreenBuilder Series

GBR50	50 CFM Fan Single Speed
GBR50L	50 CFM Fan/Light
GBR80	80 CFM Fan Single Speed
GBR80H	80 CFM Fan with Humidity Sensor
GBR80L	80 CFM Fan/Light
GBR80HL	80 CFM Fan/Light with Humidity Sensor 🔐
GBR80MHL	80 CFM Fan/Light with Humidity
	and Motion Sensor
GBR80LED	80 CFM Fan/LED Light
GBR100	100 CFM Fan Single Speed
GBR100L	100 CFM Fan/Light

Project Pack Components*

GBR-A GreenBuilder Housing Can for Fan Only

GBR50-B 50 CFM Motor/Grille GBR80-B 80 CFM Motor/Grille 100 CFM Motor/Grille GBR100-B

GBRL-A GreenBuilder Housing Can for Fan/Light

GBR50L-B 50 CFM Motor/Grille/Light 80 CFM Motor/Grille/Light GBR80L-B GBR100L-B 100 CFM Motor/Grille/Light

^{*}Project Pack components are sold in quantities of four

	Delta Breez	Market AC Motor
Energy Use (Watts)	3.8	27.1
Noise Level (Sones)	<0.3	1.5
Annual Energy Cost per Fan (24/7) ¹	\$3.99	\$28.49

¹ Calculations based upon U.S. average retail electricity and HVI testing labs. Actual results may vary

The Builders' choice for green construction

Delta BreezGreenBuilder fans mark a new achievement in bathroom ventilation for green construction. Built upon market-leading energy efficiency, exceptionally low power consumption and virtually silent operation, the adds feature options of LED main light, adjustable humidity sensing and speed control, and a 100 CFM model. Additionally, the models have enhanced performance at 0.25" static pressure. BreezGreenBuilder stays true to what has made the GreenBuilder series a winning value proposition for builders and contractors: a reliable Delta DC brushless motor, compact lightweight design for guick installation, and performance ratings that far surpass building requirements...all at an affordable price.



Fan Only & Fan with Humidity Sensor



Fan/Light, Fan/Light with Humidity Sensor, Fan/Light with Humidity and Motion Sensor



Control Options GBR80H, GBR80HL, GBR80MHL



Fan/LED light

Innovative DC brushless motor design for long life, low noise, and low power consumption

- Energy savings up to 86%²
- <0.3 sones lowest tested noise level available for bath fans
- Exceeds ENERGY STAR® requirement by 840% in energy efficiency³
- Fan/light and fan/LED light combinations and project packs available

Project Pack Components Available

















² Based upon BreezGreenBuilder G2 GBR50 vs. market AC motor fan

³ Based upon ENERGY STAR criteria for residential ventilating fans

Specifications


Fan Housing for

Delta BreezGreenbuilder G2 Perfectly quiet. Perfectly green.


The Builders' choice for green construction. Designed for easy retrofit and new construction.

GBR50, GBR80, GBR80H and GBR100

Fan/Light Housing for GBR50L, GBR80L, GBR80HL, GBR80MHL and GBR100L



Fan/LED Light Housing for GBR80LED



Grille for Fan Only

Grille for Fan/Light

Grille for Fan/LED Light

Grille for F	Grille for Fan/Light										Grille for Fan/LED Light											
Delta BreezGreenBuilder G2	GBF	R50	GBR	50L	GBF	R80 GBR80H				GBR	80L	GBR	BOHL/ GB	R80M	HL	GBR80LED		GBR100		GBR100L		
Fan Speed	Full S	peed	Full S	peed	Full S	peed	Continuous Low Speed Full Speed			Full S	peed	Continuous	Full S	speed	Full Speed		Full Speed					
Static Pressure (Inches w.g.)	0.1	0.25	0.1	0.25	0.1	0.25	0.1	0.25	0.1	0.25	0.1	0.25	0.1	0.25	0.1	0.25	0.1	0.25	0.1	0.25	0.1	0.25
Air Flow (CFM)	50	35	50	38	80	69	50	37	80	68	80	69	50	40	80	63	80	63	100	81	100	76
Sones	<0.3	0.6	<0.3	0.7	0.6	1.1	<0.3	1.0	8.0	1.2	0.8	1.3	0.4	0.6	0.8	1.3	0.8	1.1	1.4	1.3	1.4	1.3
Power Consumption (Watts)	3.8	5.2	4.5	5.8	10.5	12.5	4.0	6.0	9.7	11.8	11.0	13.6	5.3	7.0	11.5	11.4	11.6	11.1	12.6	11.6	13.9	11.9
Energy Efficiency (CFM/Watt)	13.1	6.7	11.1	6.5	7.6	5.5	12.5	6.1	8.2	5.7	7.2	5.0	9.4	5.7	6.9	5.5	6.8	5.6	7.9	6.9	7.1	6.3
Current (Amps)	0.12	Max	0.14	Max	0.22 Max 0.16 N			Max	0.22	Max	0.23	Max	0.17	Max	0.22	Max	0.30	Max	0.22 Max		0.23 Max	
Power Rating (V/Hz)		120	/ 60			120 / 60										120 / 60						
Mounting Opening		8.25"	x 8.0"			8.25"x 8.0"											8.25"x 8.0"					
Mounting Depth		5.7	75"			5.75"										5.75"						
Grille Size	10.75">	10.75"	11.0"x	(11.0"	10.75">	x 10.75" 10.75" x 10.75"					11.0" x	(11.0"	11.0" x 11.0"				10.75"	x 10.75"	10.75">	10.75"	11.0"x 11.0"	
Duct Diameter		4	"		4"									4"								
Lamp (Watts)	N/	'A	2	6	N/	/A	N/A				26	6	26				1	1	N/A		26	
Lamp Style	N/	'A	GU24	CFL 🍃	N/	'A	N/A			GU24	CFL 💡	GU24 CFL 💡			LED Mo	odule 🍨	N/A		GU24 CFL 💡			
Automatic Operation	N/	'A	N/	'A	N/	'A	Yes (humidity) 🎝				N/	'A	Yes - GBR80HL (humidity) ** Yes - GBR80MHL (humidity & motion) ** ** ** ** ** ** ** ** ** ** ** ** **					/A	N/A		N/A	
Dual Speed Operation	N/	'A	N/	/A	N/	'A	Yes (humidity) 🔩				N/	'A	Yes-G Yes-GBR80N	N.	/A	N/A		N/A				
Color Temperature	N/	'A	270	10 K	N/	'A	N/A				270	0 K	2700 K			270	00 K	N/A		2700 K		
Lumens	N/	'A	18.	50	N/	/A		N/A			185	50	1850			79	91	N/A		1850		
Shipping Gross Weight (Lbs)	7.	0	8.	.8	7.	0				8.8			8.6			7.5		7.0		8.	8.8	
cUL Tub/Shower Enclosure		Ye	es		Yes										Yes							
California Title 24 Compliant		Ye	es				Yes												Yes			
Mfg in ISO 9001 Certified Factory		Ye	es								Yes									Ye	Yes	
ENERGY STAR® Qualified		Ye	es								Ye	25							Yes			
ENERGY STAR Most Efficient 2014		Ye	es				Y	Yes					No					lo		Ye	!S	
Warranty (Years)		3	3		3									3								



Design and specifications subject to change without notice.

Motion sensor Adjustable humidity sensor** Fan/LED Light Combo**

Fan/CFL Light Combo