

POWER GAS WATER HEATER

*10L and 16L models are also available with digital panel.



POWER GAS 5L | 10L | 16L Liquid Propane Gas or Natural Gas

No electrical connection required.

- Compact design saves space and allows for easy installation just about anywhere.
- Heats unlimited volume of water as needed.
- Hot water is available in just a few seconds.
- Activates by water flow from the moment the faucet is opened.
- 5-year warranty.

Features:

- Saves water and up to 60% less electricity than conventional tank water heater, making it cost-effective and environmentally friendly.
- Can last a lifetime, keeping up to 87% efficiency level.
- Rustproof, no water loss due to leaks.



*Highest gas setting: set for Winter/High
*Lowest gas setting: set for Summer/Low

TEMPERATURE INCREASE PER GPM											
Model	Gas Setting	0.5 GPM	1.0 GPM	1.5 GPM	2.0 GPM	2.5 GPM	2.7 GPM	3.0 GPM	3.5 GPM	4.0 GPM	4.3 GPM
GA5L	Highest	129°	64°	43°	32°	-	-	-	-	-	-
	Lowest	34°	17°	11°	9°	-	-	-	-	-	-
GA10L	Highest	-	100°	67°	50°	40°	37°	30°	-	-	-
	Lowest	68°	34°	23°	17°	14°	13°	9°	-	-	-
GA16L	Highest	-	143°	95°	71°	57°	52°	48°	41°	36°	33°
	Lowest	88°	44°	29°	22°	18°	16°	15°	13°	11°	10°

TECHNICAL SPECIFICATIONS	GAS 5L	GAS 10L	GAS 16L
Hot Water Outlet per Minute	5 LPM / 1.3 GPM	10 LPM / 2.7 GPM	16 LPM / 4.2 GPM
Heat Loss	34,614 BTU/h	79,228 BTU/h	111,903 BTU/h
Activation Flow Rate	10 PSI	10 PSI	10 PSI
Maximum Flow Rate	2 GPM	3 GPM	4.3 GPM
Width x Height x Depth	11.4" x 17" x 4.7"	13.6" x 23.6" x 6.9"	16.5" x 27.9" x 8.2"
Weight	11 lbs	21 lbs	29 lbs
Gas Type	Liquid Propane Gas or Natural Gas		
Related Gas Pressure (PSI)	0.25 up to 0.5 PSI (NG) & 0.4 (LPG)		
Exhaust Discharge Mode	Flue Duct Type		
Applicable Water Pressure	3.6 - 145.0 PSI / 0.25 - 10 bar		
Ignition	2D Cell Battery Powered (not included)		
Energy Efficiency	54% - 87%		

* No need for electricity, starts with pulse ignition, powered by 2 D cell batteries.